



Barstool with upholstered shell and 4 steel legs and swivel base and finished in polished chrome, white or black.

 0,29  11,4  1

| | Back height | Seat height | Width | Depth |
|--------------|-------------|-------------|-------|-------|
| Measures mm. | 1.010 | 760 | 490 | 455 |

Frame 4-legged oval steel tube swivel base with polished chrome finish. Polished chrome oval steel tube footrest. Rotating system integrated into top of the structure. Injected aluminum plate with polished finish fixes the base to the seat. Polypropylene glides

Seat Seat with solid beech structure and polypropylene elastic straps. Flame retardant polyurethane flexible foam with a density of 25 kg/m³ and 40 kg/m³.

Back Beech plywood shell with flexible flame retardant foam with density between 25 kg/m³ and 40 kg/m³.

Other materials Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Accessories Polypropylene, felt or steel glides.

Leather

Leather

L1 High grade cow leather

L3 Polished full grain leather

L6 Aniline leather batique-effect. Scandinavian cattle.

| | | | | | |
|---------|--|--|---|---|------------------------|
| Fabrics | Fabrics / Telas | | | | Faux Leather / Ecopiel |
| | 1 Jacquard One Jacquard Three Sand Era Gravity Rivet Urban | 3 Jacquard Four Medley Revive 1 Maglia Main Line Flax Loom Two | 5 Silk Synergy Step Step Melange Messenger 5 Blazer Melange Nap Glow | 8 Capture Fiord Tonus 4 Divina 3 Lopi | |
| | 2 Jacquard Two | 4 Jacquard 4 Special Hemp Nexus Oxygen Floyd Remix 2 Heritage Savane Loom Three Loom Four | 6 Capture Fiord Tonus 4 Divina 3 Lopi | 9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3 | |
| | | | 7 Canvas 2 Rime | | |

Steel finish



| | |
|------------------------|--|
| Resistance and Quality | Indoor Air Quality-Advantage Gold |
| | ISO 9001 |
| | UNE-EN 16139 |
| Fireproof | BS 5852 Part 2 Crib 5 |
| | California Technical Bulletin 117 |
| | UNE-EN 1021-1 & 2 |
| | UNI 9175 (class 1 IM) |
| Sustainability | ISO 14001 |
| | ISO 14001 |
| | level® 2 certified to ANSI/BIFMA e3 Standard |