



Barstool with upholstered shell and steel sled base finished in polished chrome, white or black.

0,29
12,6
1

	Back height	Seat height	Width	Depth
Measures mm.	1.010	760	500	465

Frame	Sled base of 12 mm diameter steel rod.
Seat	Seat with solid beech structure and polypropylene elastic straps. Flame retardant polyurethane flexible foam with a density of 25 kg/m3 and 40 kg/m3.
Back	Beech plywood shell with flexible flame retardant foam with density between 25 kg/m3 and 40 kg/m3.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Accesories	Polypropylene, felt or steel glides.
Leather	Leather L1 High grade cow leather L3 Polished full grain leather L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics	Fabrics / Telas				Faux Leather / Ecopiel
	1 Jacquard One Jacquard Three Sand Era Gravity Rivet Urban	3 Jacquard Four Medley Revive 1 Maglia Main Line Flax Loom Two	5 Silk Synergy Step Step Melange Messenger 5 Blazer Melange Nap Glow	8 Capture Fiord Tonus 4 Divina 3 Lopi	
	2 Jacquard Two	4 Jacquard 4 Special Hemp Nexus Oxygen Floyd Remix 2 Heritage Savane Loom Three Loom Four	6 Capture Fiord Tonus 4 Divina 3 Lopi	9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3	
			7 Canvas 2 Rime		

Steel finish



Resistance and Quality	Indoor Air Quality-Advantage Gold
	ISO 9001
	UNE-EN 16139
Fireproof	BS 5852 Part 2 Crib 5
	California Technical Bulletin 117
	UNE-EN 1021-1 & 2
	UNI 9175 (class 1 IM)
Sustainability	ISO 14001
	ISO 14001
	level® 2 certified to ANSI/BIFMA e3 Standard