## **Andreu World**

**BU1522** 

Lievore Altherr Molina, S.L.



High back lounge chair with upholstered seat and backrest and a 4-legged beech wood base.







Measures	
mm.	

Seat

Back height	Seat height	Arm height	Width	Depth
1.100	420	480	750	800
1.100	430	400	750	000

Frame 4-legged beech base.

Solid beech structure with polypropylene elastic straps covered with flame retardant polyurethane flexible foam with a

density between 25 kg/m3 and 40 kg/m3.

Back Beech plywood shell with flexible flame retardant foam with density between 25 kg/m3 and 40 kg/m3.

Arms Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m3 and 40 kg/m3.

Other materials Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Accesories Polypropylene, felt or steel glides.

# **Andreu World**

**BU1522** 

Alya

Lievore Altherr Molina, S.L.

### Leather

#### Leather

- L1 High grade cow leather
- L3 Polished full grain leather
- L6 Aniline leather batique-effect. Scandinavian cattle.

### **Fabrics**

#### Fabrics / Telas

- 1 Jacquard One Jacquard Three Sand Era Gravity Rivet Urban
- 2 Jacquard Two
- 3 Jacquard Four Medley Revive 1 Maglia Main Line Flax  $Loom\,Two$
- 4 Jacquard 4 Special Hemp Nexus Oxygen Floyd Remix 2 Heritage Savane Loom Three

Loom Four

- **5** Silk Synergy Step Step Melange Messenger 5 Blazer Melange Nap
  - **6** Capture Fiord Tonus 4 Divina 3 Lopi

Glow

7 Canvas 2 Rime

### Faux Leather / Ecopiel 8 Capture

- 1 Valencia
- 2 Silvertex 4 Dolce
- 6 Ledger

### **Wood finish** Beech













Fiord Tonus 4

Divina 3

9 Divina MD Divina Melange 3

Hallingdal 65

Steelcut Trio 3

Lopi































Resistance and Quality

Indoor Air Quality-Advantage Gold

ISO 9001

UNE-EN 16139

Fireproof

BKZ 5.2

BS 5852 Part 2 Crib 5

California Technical Bulletin 117

UNE-EN 1021-1 & 2

UNI 9175 (class 1 IM)

# **Andreu World**

BU1522

**Alya** Lievore Altherr Molina, S.L.

FSC Sustainability

> ISO 14001 ISO 14001

level® 2 certified to ANSI/BIFMA e3 Standard