Andreu World

SO1491 Alya Executive Lievore Altherr Molina, S.L.



High back armchair with upholstered shell and aluminum swivel four-star base with self-return and finished in polished aluminun, white or black. Additional options include: tilting mechanism and back finished in walnut veneer.



	Back height	Seat height	Arm height	Width	Depth
Measures mm.	1.230	460	640	620	680
					_
Frame	Aluminum swivel 4-star base with self-return.				

Seat	Seat with solid beech structure and polypropylene elastic straps. Flame retardant polyurethane flexible foam with a density of 25 kg/m3 and 40 kg/m3.				
Back	Beech plywood shell with flexible flame retardant foam with density between 25 kg/m3 and 40 kg/m3. Walnut back option.				
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m3 and 40 kg/m3.				
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.				
Accesories	Polypropylene, felt or steel glides.				

Andreu World

SO1491 Alya Executive Lievore Altherr Molina, S.L.

Leather

Leather

- L1 High grade cow leather
- L3 Polished full grain leather
- L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics

Fabrics / Telas

- 1 Jacquard One Jacquard Three Sand Era Gravity Rivet Urban
- 2 Jacquard Two
- 3 Jacquard Four Medley Revive 1 Maglia Main Line Flax $Loom\,Two$
- 4 Jacquard 4 Special Hemp Nexus Oxygen Floyd Remix 2 Heritage Savane Loom Three

Loom Four

- 5 Silk Synergy Step Step Melange Messenger 5 Blazer Melange Nap
- 6 Capture Fiord Tonus 4 Divina 3 Lopi

Glow

7 Canvas 2 Rime

8 Capture Fiord Tonus 4

- Divina 3
- 9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3

Faux Leather / Ecopiel

- 1 Valencia
- 2 Silvertex 4 Dolce
- 6 Ledger

Aluminum finish







Resistance and

Indoor Air Quality-Advantage Gold

Quality

ISO 9001

UNE-EN 16139

Fireproof

BS 5852 Part 2 Crib 5

California Technical Bulletin 117

UNE-EN 1021-1 & 2 UNI 9175 (class 1 IM)

Sustainability

ISO 14001

ISO 14001

level® 2 certified to ANSI/BIFMA e3 Standard