



Fully upholstered ottoman.

0,29 12,3 1

	Seat height	Width	Depth
Measures mm.	380	700	700

Frame Curved beech plywood covered with flame retardant polyurethane flexible foam with 25kg/m3 y 40 kg/m3 density.

Seat Beech plywood shell with flexible flame retardant foam with density between 25 kg/m3 and 40 kg/m3.

Other materials Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Accessories Polypropylene, felt or steel glides.

Leather

Leather

L1 High grade cow leather

L3 Polished full grain leather

L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics	Fabrics / Telas					Faux Leather / Ecopiel					
	1	Jacquard One Jacquard Three Sand Era Gravity Rivet Urban	3	Jacquard Four Medley Revive 1 Maglia Main Line Flax Loom Two	5	Silk Synergy Step Step Melange Messenger 5 Blazer Melange Nap Glow	8	Capture Fiord Tonus 4 Divina 3 Lopi	1	Valencia	
									2	Silvertex	
	2	Jacquard Two		4	Jacquard 4 Special Hemp Nexus Oxygen Floyd Remix 2 Heritage Savane Loom Three Loom Four	6	Capture Fiord Tonus 4 Divina 3 Lopi		4	Dolce	
						7	Canvas 2 Rime		9	Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3	6
Resistance and Quality	Indoor Air Quality-Advantage Gold										
	ISO 9001										
	UNE-EN 16139										
Fireproof	BKZ 5.2										
	BS 5852 Part 2 Crib 5										
	California Technical Bulletin 117										
	UNE-EN 1021-1 & 2										
	UNI 9175 (class 1 IM)										
Sustainability	ISO 14001										
	ISO 14001										
	level® 2 certified to ANSI/BIFMA e3 Standard										