



Fully upholstered ottoman.


0,29


9,5


1

	Seat height	Width	Depth
Measures mm.	380	700	510

Frame Curved beech plywood covered with flame retardant polyurethane flexible foam with 25kg/m3 y 40 kg/m3 density.

Seat Beech plywood shell with flexible flame retardant foam with density between 25 kg/m3 and 40 kg/m3.

Other materials Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Accessories Polypropylene, felt or steel glides.

Leather

Leather

L1 High grade cow leather

L3 Polished full grain leather

L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics	Fabrics / Telas				Faux Leather / Ecopiel
	1 Jacquard One Jacquard Three Sand Era Gravity Rivet Urban	3 Jacquard Four Medley Revive 1 Maglia Main Line Flax Loom Two	5 Silk Synergy Step Step Melange Messenger 5 Blazer Melange Nap Glow	8 Capture Fiord Tonus 4 Divina 3 Lopi	
	2 Jacquard Two	4 Jacquard 4 Special Hemp Nexus Oxygen Floyd Remix 2 Heritage Savane Loom Three Loom Four	6 Capture Fiord Tonus 4 Divina 3 Lopi	9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3	1 Valencia 2 Silvertex 4 Dolce 6 Ledger
			7 Canvas 2 Rime		
Resistance and Quality	Indoor Air Quality-Advantage Gold				
	ISO 9001				
	UNE-EN 16139				
Fireproof	BKZ 5.2				
	BS 5852 Part 2 Crib 5				
	California Technical Bulletin 117				
	UNE-EN 1021-1 & 2				
	UNI 9175 (class 1 IM)				
Sustainability	ISO 14001				
	ISO 14001				
	level® 2 certified to ANSI/BIFMA e3 Standard				