



Armchair with a four star aluminum swivel base, with self-return system, and finished in polished aluminum, white or black. Upholstered seat and backrest. Optional Tilting mechanism.

 0,38  13  1

	Back height	Seat height	Arm height	Width	Depth
Measures mm.	825	460	640	625	660
Frame	4-star aluminum central swivel base with self-return system and finished in polished aluminum, white or black. Polished aluminum plate fixes the base to the seat. Central column is a 52 mm. aluminum tube with integrated self-return. Polypropylene glides.				
Seat	Seat with solid beech structure and polypropylene elastic straps. Flame retardant polyurethane flexible foam with a density of 25 kg/m3 and 40 kg/m3.				
Back	Beech plywood shell with flexible flame retardant foam with density between 25 kg/m3 and 40 kg/m3.				
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m3 and 40 kg/m3.				
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.				
Accessories	Polypropylene, felt or steel glides.				

Leather

Leather

L1 High grade cow leather

L3 Polished full grain leather

L6 Aniline leather batique-effect.
Scandinavian cattle.

Fabrics

Fabrics / Telas

1 Jacquard One
Jacquard Three
Sand
Era
Gravity
Rivet
Urban

2 Jacquard Two

3 Jacquard Four
Medley
Revive 1
Maglia
Main Line Flax
Loom Two

4 Jacquard 4 Special
Hemp
Nexus
Oxygen
Floyd
Remix 2
Heritage
Savane
Loom Three
Loom Four

5 Silk
Synergy
Step
Step Melange
Messenger 5
Blazer
Melange Nap
Glow

6 Capture
Fiord
Tonus 4
Divina 3
Lopi

7 Canvas 2
Rime

8 Capture
Fiord
Tonus 4
Divina 3
Lopi

9 Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

1 Valencia
2 Silvertex
4 Dolce
6 Ledger

Aluminum
finish



Resistance
and
Quality

Indoor Air Quality-Advantage Gold
ISO 9001
UNE-EN 16139

Fireproof

BKZ 5.2
BS 5852 Part 2 Crib 5
California Technical Bulletin 117
UNE-EN 1021-1 & 2
UNI 9175 (class 1 IM)

Sustainability

ISO 14001
ISO 14001
level® 2 certified to ANSI/BIFMA e3 Standard