



Armchair with upholstered seat and aluminum central base with 5 casters, swivel and pneumatic height adjustment. Available in polished aluminum, white or black. The chair rises to 120mm.

0,33
12,6
1

	Back height	Seat height	Arm height	Width	Depth
Measures mm.	785	420	600	625	660

Frame	Aluminum central base with 5 casters, swivel and pneumatic height adjustment. The chair rises to 120 mm.
Seat	Seat with solid beech structure and polypropylene elastic straps. Flame retardant polyurethane flexible foam with a density of 25 kg/m3 and 40 kg/m3.
Back	Beech plywood shell with flexible flame retardant foam with density between 25 kg/m3 and 40 kg/m3.
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m3 and 40 kg/m3.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Accessories	Polypropylene, felt or steel glides.

Leather	Leather
	L1 High grade cow leather
	L3 Polished full grain leather
	L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics	Fabrics / Telas				Faux Leather / Ecopiel	
	1 Jacquard One Jacquard Three Sand Era Gravity Rivet Urban	3 Jacquard Four Medley Revive 1 Maglia Main Line Flax Loom Two	5 Silk Synergy Step Step Melange Messenger 5 Blazer Melange Nap Glow	8 Capture Fiord Tonus 4 Divina 3 Lopi	1 Valencia	
	2 Jacquard Two	4 Jacquard 4 Special Hemp Nexus Oxygen Floyd Remix 2 Heritage Savane Loom Three Loom Four	6 Capture Fiord Tonus 4 Divina 3 Lopi	9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3	2 Silvertex	
			7 Canvas 2 Rime		4 Dolce	
					6 Ledger	

Aluminum finish	
	Polished aluminum
	White
	Black

Resistance and Quality	Indoor Air Quality-Advantage Gold
	ISO 9001
	UNE-EN 16139
Fireproof	BKZ 5.2
	BS 5852 Part 2 Crib 5
	California Technical Bulletin 117
	UNE-EN 1021-1 & 2
	UNI 9175 (class 1 IM)
Sustainability	ISO 14001
	ISO 14001
	level® 2 certified to ANSI/BIFMA e3 Standard