





High back lounge chair with arms, upholstered shell and aluminum swivel four-star base with self-return and finished in polished aluminum, white or black. Additional options include: parallel upholstery stitching, tilt mechanism and back finished in walnut veneer.

 0,57  19,02  1

	Back height	Seat height	Arm height	Width	Depth
Measures mm.	1.225	400	610	620	660

Frame	4-star aluminum central swivel base with self-return system and finished in polished aluminum, white or black. Polypropylene glides. Optional tilting system.
Seat	Upholstered shell with flame retardant foam with density between 25 kg/m3 and 40 kg/m3. Optional parallel stitching.
Back	Upholstered shell with flame retardant foam with density between 55 lb/ft3 and 88 lb/ft3 (25 kg/m3 and 40 kg/m3). Optional parallel stitching. Optional walnut veneer back.
Arms	Aluminum armrests.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Accessories	Felt glides.
Leather	Leather L1 High grade cow leather L3 Polished full grain leather L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics	Fabrics / Telas				Faux Leather / Ecopiel
	1 Jacquard One Jacquard Three Sand Era Gravity Rivet Urban	3 Jacquard Four Medley Revive 1 Maglia Main Line Flax Loom Two	5 Silk Synergy Step Step Melange Messenger 5 Blazer Melange Nap Glow	8 Capture Fiord Tonus 4 Divina 3 Lopi	
	2 Jacquard Two	4 Jacquard 4 Special Hemp Nexus Oxygen Floyd Remix 2 Heritage Savane Loom Three Loom Four	6 Capture Fiord Tonus 4 Divina 3 Lopi	9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3	1 Valencia 2 Silvertex 4 Dolce 6 Ledger
			7 Canvas 2 Rime		
Aluminum finish					
	Polished Aluminum				
Aluminum finish					
	EPXB White EPXN Black				
Resistance and Quality	Indoor Air Quality-Advantage Gold ISO 9001 UNE-EN 16139				
Fireproof	BKZ 5.2 BS 5852 Part 2 Crib 5 California Technical Bulletin 117 UNE-EN 1021-1 & 2 UNI 9175 (class 1 IM)				
Sustainability	ISO 14001 ISO 14001 level® 1 certified to ANSI/BIFMA e3 Standard				