



High back chair with upholstered shell and height adjustable central swivel base with 5 casters finished in polished aluminum, white or black. Additional options include: parallel upholstery stitching, tilt mechanism and back finished in walnut veneer. The piston increases 100 mm.

 0,57  14,62  1

	Back height	Seat height	Width	Depth
Measures mm.	1.265	440	665	665

**Frame** Central aluminum base with 5 casters, swivel and height-adjustable and finished in polished aluminum, white or black. The piston raises 100 mm. Optional tilting system.



**Seat** Upholstered shell with flame retardant foam with density between 25 kg/m3 and 40 kg/m3. Optional parallel stitching. Optional walnut veneer back.

**Back** Upholstered shell with flame retardant foam with density between 25 kg/m3 and 40 kg/m3. Optional parallel stitching. Optional walnut veneer back.

**Other materials** Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

**Accessories** Polypropylene, felt or steel glides.

**Leather**  
**Leather**  
**L1** High grade cow leather  
**L3** Polished full grain leather  
**L6** Aniline leather batique-effect. Scandinavian cattle.

Fabrics	Fabrics / Telas				Faux Leather / Ecopiel
	1 Jacquard One Jacquard Three Sand Era Gravity Rivet Urban	3 Jacquard Four Medley Revive 1 Maglia Main Line Flax Loom Two	5 Silk Synergy Step Step Melange Messenger 5 Blazer Melange Nap Glow	8 Capture Fiord Tonus 4 Divina 3 Lopi	
	2 Jacquard Two	4 Jacquard 4 Special Hemp Nexus Oxygen Floyd Remix 2 Heritage Savane Loom Three Loom Four	6 Capture Fiord Tonus 4 Divina 3 Lopi	9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3	1 Valencia 2 Silvertex 4 Dolce 6 Ledger
			7 Canvas 2 Rime		
Aluminum finish					
	Polished Aluminum				
Aluminum finish					
	EPXB White      EPXN Black				
Resistance and Quality	Indoor Air Quality-Advantage Gold				
	ISO 9001				
	UNE-EN 16139				
Fireproof	BKZ 5.2				
	BS 5852 Part 2 Crib 5				
	California Technical Bulletin 117				
	UNE-EN 1021-1 & 2				
	UNI 9175 (class 1 IM)				
Sustainability	ISO 14001				
	ISO 14001				
	level® 1 certified to ANSI/BIFMA e3 Standard				